

Safe contact with the compact earthing clamp

The small active earthing clamps in the 70 series have very hard and sharp jaws. The compact clamp has a high closing force, ensuring a secure connection for potential equalization at all times. The 70HK is specially designed for earthing BIG-BAGs with 2 clamps.

Advantages at a glance

- > compact size
- > suitable for mounting on smaller containers, or BIG-BAG (70HK)
- > hard and sharp clamp jaws
- > permanently high clamping force







	Technical Information	
Versions	70AK	70HK
Enclosure Material	Stainless steel	Galvanized sheet steel, plastic handles
Operating ambient temperature	-40 +70°C	-20 +70°C (-4 +158°F)
Ambient humidity	max. 80% rel. humidity, non-condensing	
Connection	Permanently connected cables, grounding cable with plug/coupling	
Protection class	Connected 4-pin plug IP67 according to EN 60529w	
Dimensions (LxWxD)	162 x 30 x 85 mm	160 x 30 x 100 mm
Weight	0.30 kg	0.25 kg
Approval, Marking	ATEX: DMT OO ATEX E 068 X Ex II 2D Ex ia IIIC T135°C Db II 2G Ex ia IIC T6 Gb	
	IECEx: BVS 16.0016X	
	Ex ia IIIC T135°C Db	
	Ex ia IIC T6 Gb	

