



ellex

electrostatic
innovations



TERRACLAMP

Secure contact thanks to strong grip

The active grounding clamps in the **TERRACLAMP** series have extremely hard and sharp jaws. The clamps also have a permanently high closing force, ensuring a secure connection for equipotential bonding at all times.

Advantages at a glance

- › innovative, ergonomic design
- › extremely hard and sharp contact elements (replaceable)
- › permanently high clamping force
- › light signal via correct earth connection on the pliers (optional)





Technical Information

Versions	Standard (S), with row of teeth (T), BIG-BAG (B), capacity measurement (C) each with or without LED earthing indicator
Enclosure Material	Stainless steel, PP
Operating ambient temperature	with coupling: -40 ... +70°C, with fixed cable: -30 ... +70°C
Ambient humidity	max. 80% rel. humidity, non-condensing
Connection	with integrated coupling plug or permanently connected cable
Protection class	IP67 according to EN 60529
Dimensions (LxWxD)	185 x 38 x 84 mm
Weight	0.35 kg
Approval, Marking	ATEX: BVS 20 ATEX E 017 X Ex II 1G Ex ia IIC T4 Ga II 1D Ex ia IIIC T135°C Da IECEX: BVS 20.0012.X Ex ia IIC T4 Ga Ex ia IIIC T135°C Da

Dimensions

