



eltex

electrostatic
innovations




TERRACORD

Rewinding cable reels – tidy and protected connection

With the 601KR cable return reels, the earthing cable is simply rolled up after use and thus protected from damage and stored safely. The cable return reels are made from impact-resistant aluminum and are swivel-mounted with a mounting bracket.

Advantages at a glance

- the grounding cable is protected and tidy
- Stop function can be switched on/off
- robust, industrial-grade housing
- 12 or 20 m cable length depending on version





Technical Information

Versions	601KR/AW20	601KR/DW12
Enclosure Material	Aluminum ribbed and reinforced, Plastic	Aluminium, Plastic
Operating ambient temperature	-40 ... +70°C	
Ambient humidity	max. 80% rel. humidity non-condensing	
Connection cable to the grounding device	3 meter, grounding cable, 3 x 1.5 mm ² , color light blue	
Assembly	Wall mounting via mounting bracket	
Dimensions (LxWxD)	20 meters oil and petrol resistant Grounding cable	12 meters oil and petrol resistant Grounding cable
Weight	approx. 14 kg	approx. 5.7 kg
Approval, Marking	ATEX: DMT 00 ATEX E 068 X Ex II 2D Ex ia IIIC T135°C Db II 2G Ex ia IIC T6 Gb IECEX: BVS 16.0016X Ex ia IIIC T135°C Db Ex ia IIC T6 Gb	

Dimensions

